

Solvent Cleaner for Epoxy Resins

## DESCRIPTION

TamRez Cleaner is specially designed to clean all TamRez epoxy systems prior to the resin setting and to clean Tam Hydroband tape prior to installation.

## KEY BENEFITS

- > Dissolves uncured epoxy resins
- > Cleans off oil and grease with ease
- > Supplied in easy to use 5 litre drums with spout
- > Cleans injection equipment
- > Can be used as a thinner if required

## TYPICAL APPLICATIONS

- > Cleaning of injection equipment
- > The preparation of PVC and Hypalon tapes
- > Removing of spilled materials
- > Cleaning of tools

## TECHNICAL DATA

TamRez Cleaner	
Density	0.85
Colour	Clear
Viscosity	1 mPa·s
Flash point	15°C
Solubility in water	Partially

All technical data stated herein is based on tests carried out under laboratory conditions.

## APPLICATION GUIDELINES

Always clean equipment before the resin has set. Tools can be immersed in TamRez cleaner prior to wiping off with a clean cloth or scrubbing with a brush.

Injection equipment must first be purged of all excess Epoxy resin and then cleaned well with TamRez cleaner.

Note: the waste product should not be discharged into the sewer and must be disposed of according to local regulations / guidelines.

## STORAGE

TamRez cleaner should be stored at room temperature (min 10°C and max 38°C), kept dry and out of direct sunlight. If these conditions are maintained and the product packaging is unopened, then a shelf life of one year can be expected.

Note: this product is flammable and local authority guidelines must be obeyed.

## HEALTH & SAFETY

TamRez Cleaner should only be used as directed. We always recommend that the Safety Data Sheet (SDS) is carefully read prior to application of the material. Our recommendations for protective equipment should be strictly adhered to for your personal protection. The Health & Safety data sheet is available upon request from your local Normet representative.