

Fixed Bollard 750mm Above Ground 60mm - 193mm Diameter Galvanised & Yellow - Bolt Down



The complete range of Plain Round Bollards is available in diameters from 60mm to 193mm and is available with extended legs for casting into concrete or with a flange plate for bolting down.

Additional colour coated options and removable versions are also available.

<u>Part Number</u>	<u>Diameter</u>	<u>Weight (kg</u>
138 121 103Y	60mm Galvanised & Yellow	4kg
138 121 256Y	76mm Galvanised & Yellow	5kg
138 121 278Y	90mm Galvanised & Yellow	6kg
138 121 327Y	101mm Galvanised & Yellow	7kg
138 121 434Y	114mm Galvanised & Yellow	8kg
138 121 554Y	127mm Galvanised & Yellow	9kg
138 121 626Y	139mm Galvanised & Yellow	17kg
138 121 654Y	152mm Galvanised & Yellow	11kg
138 121 724Y	168mm Galvanised & Yellow	18kg
138 121 784Y	193mm Galvanised & Yellow	20kg

Product details

- 3mm wall thickness 60mm-127mm and 152mm
- 5mm wall thickness 139mm, 168mm, and 193mm
- 3 hole round plate 133mm x 5mm 60mm & 76mm diameters
- 3 hole round plate 180mm x 5mm 90mm 114mm diameters
- 4 hole square plate 250mm x 10mm 127mm 193mm diameters

Installation & use

Bolt down to a suitable concrete surface. Telescopic, removable and concrete in are supplied with welded fixing spikes to ensure firm ground anchorage into concrete. Telescopic, removable and concrete in require a suitable excavated hole for installing into concrete. Products are guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk +44 (0)1788 550556

ISO 9001 Sion 14001 Sion 140

AUTOPA Limited Cottage Leap, Rugby, Warwickshire CV21 3XP