

GFC2R 1000mm Galvanised or Galvanised & Colour

The GFC 2R Ornamental Mild Steel Bollard from AUTOPA is suitable for a wide range of locations and purposes. The main post is constructed using mild steel, galvanised to ensure its longevity. Two cast iron rings are welded onto the steel tube to complete the design.

The bollards are available in a galvanised and galvanised and coated finish. RAL numbers must be specified at time of order. Eyelets, hooks and chains can be added to these bollards to complete the decorative effect. Please ask for more information.

| <u>Part Number</u> | Description | <u>Lift Weight (kg)</u> | <u>Weight (kg)</u> |
|--------------------|-----------------------------------|-------------------------|--------------------|
| 138 120 151 | Galvanised - Concrete In | | 13kg |
| 138 120 152 | Galvanised & Black - Concrete In | | 13kg |
| 138 120 153 | Galvanised & Colour - Concrete In | | 13kg |
| 138 120 154 | Galvanised - Bolt Down | | 13kg |
| 138 120 155 | Galvanised & Black - Bolt Down | | 13kg |
| 138 120 156 | Galvanised & Colour - Bolt Down | | 13kg |
| 138 120 157 | Galvanised - Removable | 13kg | 21kg |
| 138 120 159 | Galvanised & Black - Removable | 13kg | 21kg |
| 138 120 158 | Galvanised & Colour - Removable | 13kg | 21kg |

Product details

- 1000mm height above ground
- 114mm diameter
- 3mm wall thickness

- Concrete in 400mm (below ground)
- Price excludes fixing down bolts and padlock to secure
- Socket 300mm (below ground)

Installation & use

Bolt down to a suitable concrete surface. Telescopic, removable and concrete in are supplied with welded fixing spikes to ensure firm ground anchorage into concrete. Telescopic, removable and concrete in require a suitable excavated hole for installing into concrete. Products are guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk +44 (0)1788 550556

AUTOPA Limited Cottage Leap, Rugby, Warwickshire CV21 3XP



