

DESIGN . SUPPLY . INSTALL







The PROCTER Height Restrictor (Fixed)

The PROCTER Height Restrictor (Fixed) is designed to restrict access to high sided vehicles such as HGV's and Caravans, they are especially useful where further height restrictions within the site may cause problems. The standard clearance is 2.05m (+/- 70mm). The Height Restrictor is constructed of heavy duty 90mm square steel with a 400mm square 10mm thick base plate. The steel is galvanised to ensure longevity and painted red (other colours available, on request). The knocking bar (where fitted) is 48mm diameter tube, painted white with red reflective bands.

The Height Restrictor is available in both a Ragged (for casting in to new concrete) and Flanged feet (for bolting to existing concrete), and is also available in galvanised and galvanised & coated finishes without the knocking bar.

Product Range

Order Code	Description
138 106 530	3.0m Height Restrictor Fixed - Flanged, including knocking bar (Galvanised & Coated)
138 106 540	4.0m Height Restrictor Fixed - Flanged, including knocking bar (Galvanised & Coated)
138 106 550	5.0m Height Restrictor Fixed - Flanged, including knocking bar (Galvanised & Coated)
138 106 560	6.0m Height Restrictor Fixed - Flanged, including knocking bar (Galvanised & Coated)
138 106 570	7.0m Height Restrictor Fixed - Flanged, including knocking bar (Galvanised & Coated)

(All sizes are measured between the inner edges of the Flanges)

Please refer to the Price List for the full range.

Accessories & installation parts

138 106 287	'MAX. HEIGHT 2.05 METRES' Warning Sign
138 100 990	M16 Foundation Bolt (4 required per barrier)

Product details

Standard Clearance; 2.05m (+/- 70mm) Base Plate; 400mm x 400mm x 10mm.

Main Tube; 90mm x 90mm. Galvanised steel, painted Red.

48mm knocking bar, coated white with Red Reflective Tape.

Installation & use

The Height Restrictor (Fixed) requires bolting down to a suitable concrete surface (not less than 600mm cubed) by means of four 16mm anchor bolts.

It is recommended that suitable signs are placed to ensure vehicles are aware of the obstruction.

This product is guaranteed for 12 months (if installed and used correctly).

Tel Sales: 02920 855756 - Fax: 02920 887005 - Email: Enquiries@ProcterContracts.co.uk