MaxiTrack



EASY TO HANDLE

Lightweight 40kg mats easily handleable with 2 workers.

TOUGH

Unique Zetralene™ plastic for maximum impact resistance.

EXTRA STRONG GRIP

Unique SmartGrip™ tread gives superior grip in all directions.

MUD SUPPRESSION

Flanged joints suppress mud seepage and enable heat expansion.



*FAST, EASY, ECONOMICAL: Install approximately 60 mats per hour with a team of 4 plus a forklift driver.

GroundGuards®

+44 (0)113 267 6000 info@ground-guards.co.uk www.ground-guards.co.uk

MaxiTrack











Material: Zetralene™ (HDPE family) recycled plastic,

fully recyclable

Overall size: 1900 x 1000 x 32mm

Nominal size: 1800 x 900 x 23mm

Surface Area: 1.62m²

Weight: 40kg

Packed in: Stillage

of 25 mats

Stillage Pack: Weight: 1130kg

Dimensions:

2110 x 1030 x 1090mm

Connectors: 6 self-aligning shoulder bolts

Slip testing: BS7976 part 2

Deflection: Tested on varying CBR ground conditions using a 300mm diameter steel

platen with 6 tonnes load to simulate the pressure of an HGV wheel.

Ground CBR 11.35%: Deflection 7.71mm

Ground CBR 8.58%: Deflection 8.66mm

Ground CBR 4%: Deflection 9.46mm

Installation rate: Install approximately 60 mats per hour

with a team of 4 plus a forklift driver

Guarantee:

It is the user's responsibility to assess the load-bearing capacity of the ground, and to only operate vehicles within the weight that the ground is capable of safely supporting. Ground-Guards Ltd accepts no liability whatsoever for any damage, loss or injury arising from the ground conditions on which these products are used.

MaxiTrack mats are not suitable to use for bridging purposes. Damage caused by mechanical equipment (e.g. cuts by digger buckets) or sharp protrusions beneath the mats is not covered by this guarantee.



+44 (0)113 267 6000 info@ground-guards.co.uk www.ground-guards.co.uk