



Rondo Railings

Generated on 02.10.2017

Detailed description

Rondo railings use circular section (CHS) verticals with rectangular hollow section (RHS) horizontal rails and posts, decorative heads are added to the pales and posts, along with optional additional rails and infills making a decorative and secure boundary fence.

Heights up to 3 m available.

Applications:

- Schools.
- Perimeter demarcation and security.
- Offices.
- Parks.
- Playgrounds.
- Residential.

Product guidance - As Standard

Bay width:

2750 mm.

Railing height:

Available heights: 1.0, 1.2, 1.5, 1.8, 2.0, 2.4 or 3.0 m.

Top and bottom rail:

50 x 25 mm.

Mid rail:

- 1.0, 1.2 or 1.5 m high: 40 x 10 mm.
- 1.8, 2.0, 2.4 or 3.0 m high: 50 x 10 mm.

Bars (tubular and solid):

Varies depending on height, consult manufacturers literature for details.

Options

Colour/ Finish:

Available hot dipped galvanized and coated polyester powder coated in any colour.

Product specification

Manufacturer

Procter Contracts

Procter Contracts
11 Pantglas Industrial Estate
Bedwas
Caerphilly
Cardiff
CF83 8XD

Tel: +44 (0)0808 2745 512

www.proctercontracts.co.uk
riba@proctercontracts.co.uk



- Name: Procter Contracts
- Web: www.proctercontracts.co.uk
- Email: riba@proctercontracts.co.uk
- Tel: +44 (0)0808 2745 512
- Fax: +44 (0)2920 887 005
- Address: 11 Pantglas Industrial
Estate, Bedwas, Caerphilly, Cardiff CF83 8XD

Product reference Rondo Railings RL-RD-507

Size As drawing - Insert details.
As schedule - Insert details.

Colour/ Finish Hot dip galvanized
Polyester powder coated, RAL - Insert
colour requirements.