



LADDERS

# Roof Edge Protection

To fully comply with work at Height Regulations 2005 handrails should be provided to prevent falls.

Bilco can now offer a system that provides a permanent or temporary solution but without the need to mechanically fix the system to the roof itself. This design overcomes the problems often associated with permanent fixing which can damage the roof membrane often causing water penetration and costly damage.

This system is a free-standing guard rail system and so it can be installed without affecting the integrity of the roof, it is intended for use as Permanent Roof Edge Protection.

## KEY ADVANTAGES

- Aesthetically pleasing
- Maintenance-free
- No structural fittings
- Recycled rubber counterweights.

The height of the guardrail is set at 1100mm. All vertical supports are set at no more than 2.5m centres with counter weights set at no more than 5m centres on a straight run.

Counterweights are manufactured from recycled rubber, reducing any abrasion on the roof.

## FEATURES

- Legs rotate 180 degrees and are telescopic or totally removable for complete roof access beneath the system
- Grub screw fixing for speed of installation
- Swept corners enhance the aesthetical appeal of the system and can maintain the architectural lines of the roof.



### ROOFEP-1

Galvanised steel handrail (including free-standing posts)

### ROOFEP-2

Galvanised steel free-standing end including rubber counterweight



Bilco UK Ltd, Pavilion 7, Fornham Business Court, Hall Farm  
Fornham St. Martin, Bury St. Edmunds, Suffolk, IP31 1SL

+44 (0)1284 701 696 bilcok@bilco.com www.bilcok.co.uk

Bilco UK is part of the Access 360 portfolio of Tyman UK and Ireland