



Specialists in Roofing  
and Waterproofing

# **ParaFlex** FD Drag Strip

## Product Data Sheet



---

Debonding tape used to create a slip joint or expansion joint beneath ParaFlex FD.

# ParaFlex

## FD Drag Strip

### General Information

**ParaFlex Drag Strip** is a debonding tape used to create a slip joint or expansion joint beneath ParaFlex FD.

### Installation instructions

Placed **ParaFlex Drag Strip** in the freshly applied ParaFlex primer with the laminated side (PE film) down. After hardening of the ParaFlex primer further laminate strips can be placed or formed over the joints.

### Delivery conditions

**Delivery form** Individual rolls.

### Storage and transport

It is essential that the product be protected from moisture. Unlimited shelf life if stored correctly.

### PRODUCT DESCRIPTION

Appearance to top side	Black Nonwoven 100 % PES 85 g/m <sup>2</sup>
Appearance to bottom side	White Foil PE/PA/PE, 40μ

### DECLARED PERFORMANCE

Essential characteristics	Performance	Units	Tolerance	Test Method
Roll length	50.0	m	-	-
Roll width	0.10	m	-	-
Dense/ Particular emphasis	125	g/cm <sup>3</sup>	-	-
Maximum tensile force				
longitudinal	160	N/5 cm	-	-
transverse	170	N/5 cm	-	-
Strain				
longitudinal	45	%	-	-
transverse	75	%	-	-

This information given in good faith and is based on the latest knowledge available to Radmat Building products Ltd. Whilst every effort has been made to ensure that the contents of the publication are current while going to press, customers are advised that products, techniques and codes of practice are under constant review and liable to change without notice.

For further information on Radmat products and services please call **01858 410372**, email [techenquiries@radmat.com](mailto:techenquiries@radmat.com) or visit our website [www.radmat.com](http://www.radmat.com) **NOV 2019**