

ReadySeal Pre-wipe Kit

Product Data Sheet



ReadySeal

Pre-wipe Kit

General Information

Pre-Wipe Kit contains specially selected cloths and high performance solution in a trigger spray that removes contaminants from the surface of ReadySeal prior to the application of ReadySeal Surface Primer.

ReadySeal Pre-wipe Kit should be used whenever applying new ReadySeal to ReadySeal that has been allowed to cure for more than 9 hours.

Designed specially for use with ReadySeal.

Directions of Application

Sweep clean the surface of the existing ReadySeal to be wiped, typically this is the overlap area between applications, at penetrations or when repairing 3rd party damage.

Wipe the surface of the ReadySeal to be primed with the **ReadySeal Pre-wipe Spray**, a minimum 100mm wide area must be sprayed at the overlap or around a penetration or the point of damage.

Ensure the cloth being used to wipe the ReadySeal is clean. Use the ReadySeal cloth to wipe off the ReadySeal Pre-wipe Spray after 30 - 40 seconds. Dispose of the cloth when dirty.

Allow the surface to completely dry before applying ReadySeal Surface Primer or ReadySeal.

Always test on a small hidden portion of the surface to be cleaned to check compatibility and performance before commencing with the whole area.

Do not use below 5°C or above 30°C.

Delivery Conditions

Delivery form

Box of 2

Storage and shelf life

Keep in a dry place between 5°C and 30°C in the original container.

| DECLARED PERFORMANCE | | |
|-------------------------|---|------|
| Product specifications | Value | Unit |
| Colour | Colourless | - |
| Odour | Faint/Characteristic | - |
| Form | Liquid | - |
| Specific Gravity @ 25°C | 0.951 | - |
| Shelf Life | 24 months from the date of manufacture in the original unopened container | - |

This information given in good faith and is based on the latest knowledge available to Radmat Building products Ltd. Whilst every effort has been made to ensure that the contents of the publication are current while going to press, customers are advised that products, techniques and codes of practice are under constant review and liable to change without notice.

For further information on Radmat products and services please call 01858 410372, email techenquiries@radmat.com or visit our website www.radmat.com

DEC 20

